

AQUENCE LA 910

Known as Adhesin VP 910 HB

March 2017

PRODUCT DESCRIPTION

AQUENCE LA 910 provides the following product characteristics:

Technology	Synthetic Resin Dispersion
Product Type	Synthetic adhesive medium viscous
Application	Packaging Industry Labeling

Application Areas

AQUENCE LA 910 is a synthetic adhesive specially developed as labeling adhesive for LANGUTH machines.

Technical Data

AQUENCE LA 910:

Viscosity, Brookfield - RVT, 7/20/23, mPas	47,000 to 53,000
ISO 2555	
pH value	5 to 9
ISO 976	

DIRECTIONS OF USE

Preliminary Statement

Prior to application it is necessary to read the Safety Data Sheet for information about precautionary measures and safety recommendations. Also, for chemical products exempt from compulsory labeling, the relevant precautions should always be observed. Please also refer to the local safety instructions and contact Henkel for analytical support.

Application

Most suitable processing temperature: 18 - 25 °C.

Dilution

AQUENCE LA 910 is ready to use and should not be diluted.

Cleaning

Uncured adhesive residues can easily be removed with water.

Handling Information

Due to the variety of different materials available on the markets pre-tests should be carried out.

STORAGE

Protect from freezing.

Close containers thoroughly after use.

When stored in a dry and cool place in the original unopened containers shelf life is as follows.

Shelf life

Shelf-life (in unopened original packaging), months	6
Recommended Storage Temperature, °C	15 to 35

Classification:

Please refer to the corresponding safety data sheets for details on:

Hazardous Information

Transport Regulations

Safety Regulations

ADDITIONAL INFORMATION

Disclaimer

Note:

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. The product can have a variety of different applications as well as differing application and working conditions in your environment that are beyond our control. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

In case products are delivered by Henkel Belgium NV, Henkel Electronic Materials NV, Henkel Nederland BV, Henkel Technologies France SAS and Henkel France SA please additionally note the following:

In case Henkel would be nevertheless held liable, on whatever legal ground, Henkel's liability will in no event exceed the amount of the concerned delivery.

In case products are delivered by Henkel Colombiana, S.A.S. the following disclaimer is applicable:

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

In case products are delivered by Henkel Corporation, Resin Technology Group, Inc., or Henkel Canada Corporation, the following disclaimer is applicable:

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability for the user's purpose of any production methods mentioned herein and to adopt such precautions as may be advisable for the protection of property and of persons against any hazards that may be involved in the handling and use thereof. In light of the foregoing, **Henkel Corporation specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation specifically disclaims any liability for consequential or incidental damages of any kind, including lost profits.** The discussion herein of various processes or compositions is not to be interpreted as representation that they are free from domination of patents owned by others or as a license under any Henkel Corporation patents that may cover such processes or compositions. We recommend that each prospective user test his proposed application before repetitive use, using this data as a guide. This product may be covered by one or more United States or foreign patents or patent applications.

Trademark usage: [Except as otherwise noted] All trademarks in this document are trademarks and/or registered trademarks of Henkel and its affiliates in the U.S. and elsewhere.

Reference 0.3

Product Description	ADQUENCE LA 910 provides the following product characteristics:
Product Type	Synthetic Resin Dispersion
Application	Labeling

Technical Data
 ADQUENCE LA 910
 Viscosity: Brookfield - RV7, 100 RPM, 25°C: 180 cSt
 pH value: 8.0-8.5

DIRECTIONS OF USE
 Preliminary Statement
 Prior to application it is necessary to read the Safety Data Sheet for information about precautionary measures and safety recommendations. Also see chemical products expert from company labeling the relevant conditions (which always be observed. Please also refer to the local safety instructions and contact Henkel for analytical support.

Application
 Most suitable processing temperature: 18 - 25 °C

Cleaning
 Unbound adhesive residues can easily be removed with water.

Handling Information
 Due to the variety of different materials available on the market the tests should be carried out.

Henkel AG & Co. KGaA
 40191 Düsseldorf, Germany
 Phone: +49-211-797-0

Henkel Corporation
 Bridgewater, NJ 08807, USA
 Phone: +1-908-685-7000

Henkel (China) Co.Ltd.
 201203 Shanghai, China
 Phone: +86-21-2891-8000